## 800MHz DIVERSITY WIRELESS TUNER UNIT DU-850A

POWER SUPPLY DC12V (Supplied from built-in equipment)

CURRENT CONSUMPTION Approx. 100mA

RECEIVING FREQUENCY 806.125MHz~809.750MHz (30 channels at 125kHz intervals)

RECEIVING SCHEME PLL control superheterodyne

RECEIVING SENSITIVITY 20dB  $\mu$  V or less (at S/N 50dB  $\pm$ 5kHzFM)

SQUELCH SENSITIVITY  $18dB \mu V$ RATED OUTPUT -30dBV

DISTORTION 3% or less (at  $\pm 40$ kHzFM)

FREQUENCY RESPONSE 50Hz $\sim$ 15kHz (1kHz basis 50  $\mu$ s emphasis)


FINISH Case (Plating steel):


DIMENSIONS 63(W) x 16(H) x 122(D) mm


MASS Approx. 140g

ACCESSORIES Channel setting driver x 1, Instruction manual x 1
APPLICABLE MICROPHONE UNI-PEX 800MHz band wireless microphone

APPLICABLE PRODUCT Wireless amplifier WA-862A series, Mixer amplifier for vehicle NX-9500







番号 名 杯 1 チャンネル設定スイッチ 2 グループ設定スイッチ

Unit: mm

BUSINESS

**AJ05**